

ALKON a brand name associated with quality for decades, introduces for the first time in India, continuous roll formed **GALVANIZED STEEL FLOOR GRATINGS**.

Manufactured using state of the art CNC controlled punching and roll forming machines.


Gratings can be used as shelves in every racking system i.e. Pallet Racking, Cantilever Racking or Mezzanine Flooring.

Gratings can be used as walkways in any racking structure.

Being manufactured by continuous roll forming process, we can offer gratings in single piece without joint up to six meters in length as standard (Pitch of the grating is 60mm and multiples thereof) and even longer lengths up to ten meters in length for special orders.

Advantages of Alkon's Galvanized Steel Floor Gratings are :


- Unique design of Grating having maximum load bearing capacity.
- High level of perforation results in sprinkler suitability for higher fire safety.
- Punched perforation on Grating surface with deep forming gives added strength.
- Bridging of large spans.
- Light and water permeability.
- Extremely fast assembly.



Please Note :
These gratings are not designed for hand pallet truck operation.



AFLG 200



Art No : **: AFLG 200**
 Size : 200mm (W) X 40mm (H) X 1.5mm (T)
 Material : Galvanized Steel as per IS 277-92
 Coating : Zinc Coated 120 gsm skin pass
 zero spangle.


Steel Thickness : 1.5mm
 Weight Per Meter : 3.388 kgs. (Approx.)
 Standard Length : In multiples of 60mm pitch max
 up to 6 meters in length as
 standard (longer lengths available
 on special request).

AFLG 200
Steel Floor Grating Load Chart

Size in mm.	Unsupported Span in mm	Safe Working Load Kg/M ²	Deflection
200 (W) X 40 (H) X 1.5 (T)	1020	800	L/180
200 (W) X 40 (H) X 1.5 (T)	1200	600	L/180

All dimensions in mm approx.

AFLG 225



Art No : **: AFLG 225**
 Size : 225mm (W) x 40mm (H) x 1.5mm (T)
 Material : Galvanized steel as per IS 277-92
 Coating : Zinc coated 120 gsm skin pass
 zero spangle.

Steel thickness : 1.5mm
 Weight per meter : 3.666 kgs. (Approx.)
 Standard length : In multiples of 60mm pitch max
 up to 6 meters in length as
 standard (longer lengths available
 on special request).

AFLG 225
Steel Floor Grating Load Chart

Size in mm	Unsupported Span in mm	Safe Working Load Kg/M ²	Deflection
225 (W) X 40 (H) X 1.5 (T)	1020	750	L/180
225 (W) X 40 (H) X 1.5 (T)	1200	550	L/180

All dimensions in mm approx.