



**R
E
A
C
H

L
I
F
T

T
R
U
C
K**

Model		QCD 10B	QCD 10C
Load Capacity	Q (kg)	1000	1000
Load Center	c (mm)	500	500
Max. Lift Ht.	h1 (mm)	5000	6200
Free Lift	h2 (mm)	1700	1900
Fork length	l1 (mm)	1070	1070
Overall height	h3 (mm)	2240	2640
Overall Length	l1 (mm)	2410	2410
Overall width	b1 (mm)	1020	1020
Intersecting Aisle pallet (1000 x 1200)	Ast (mm)	2800	2800
Tyre Poly Urethane, Front / Rear	- (mm)	250 / 230	250 / 230
Truck Weight	- (Kg)	2500	2600
Battery	V/Ah	48 / 400	48 / 400
Side Shift		INCLUDED	
Brake		ELECTRO MAGNETIC	
Controller		MOSFET	
Steering		HYDROSTATIC	

ALSO AVAILABLE IN 1500 KG & 2000 KG CAPACITY

Model		CPD 10S	CPD 10S
Load Capacity	Q (kg)	1000	1600
Load Center	c (mm)	500	500
Max. Lift Ht.	h1 (mm)	3500	3500
Free Lift	h2 (mm)	0	150
Fork length	l (mm)	900	900
Carriage Width	b3 (mm)	900	980
Overall height	h3 (mm)	2400	2400
Overall Length	l1 (mm)	2500	2750
Overall width	b1 (mm)	1020	1100
Intersecting Aisle pallet (1000 x 1200)	Ast (mm)	2980	3160
Tyres Elastic Solid, Front	- (mm)	4.00 x 8	18.7 x 8
Tyre Poly Urethane, Rear	- (mm)	280 / 100	16.6 x 10.5
Service Weight	(kg)	2180	2800
Battery	V/Ah	24 / 400	48 / 360
Side Shift		INCLUDED	
Brake		ELECTRO MAGNETIC	
Controller		MOSFET	
Steering		HYDROSTATIC	
Mast		FULL VIEW TYPE	
TILING FRONT / BACK	/	5 / 10	3 / 6

ALSO AVAILABLE IN 2000 KG CAPACITY



3 WHEEL ELECTRIC FORKLIFT